

# Autologin auf Cisco-Switch mittels expect

Dieses Script ermöglicht einen automatischen Login auf Cisco-Switches inkl. automatischem „enable“ (sofern die beiden Kennwörter gleich sind).

```
#!/usr/bin/expect -f
#####
## Update Router Config
#####
set host [lindex $argv 0]
set pw XXXX
trap exit {SIGINT SIGTERM}
spawn telnet $host

expect {
  "Username: " {
    send "root\r"
    exp_continue
  }
  "Password: " {
    send "$pw\r"
  }
  timeout {
    send_user "\n\ntimeout...\n"
    exit 1
  }
}

expect {
  "% " {
    send_user "\n\nlogin failed.\n"
    exit 1
  }
  ">" {
    send "enable\r"
  }
}
```

```
expect {
  "Password: " {
    send "$pw\r"
  }
  timeout {
    send_user "\n\ntimeout...\n"
    exit 1
  }
}

expect {
  "% " {
    send_user "\n\nenable failed.\n"
    exit 1
  }
  "#" {
    send_user "\nlogged in...\n"
    send "\n"
  }
}

interact
```

---

Revision #2

Created 2021-05-31 14:34:31 UTC by magenbrot

Updated 2021-05-31 14:35:07 UTC by magenbrot