

# packages.gitlab.com (Gitlab)

## gitlab-ce

```
apt update
apt install -y curl ca-certificates apt-transport-https gnupg2
curl --location "https://packages.gitlab.com/install/repositories/gitlab/gitlab-
ce/script.deb.sh" | bash
apt update
EXTERNAL_URL="https://gitlab.example.com" apt install gitlab-ce
# or
# GITLAB_ROOT_EMAIL="admin@example.com" GITLAB_ROOT_PASSWORD="strongpassword"
EXTERNAL_URL="https://gitlab.example.com" apt install gitlab-ce
cat /etc/gitlab/initial_root_password
```

from <https://docs.gitlab.com/install/package/debian/>

## gitlab-runner

```
curl -L "https://packages.gitlab.com/install/repositories/runner/gitlab-runner/script.deb.sh"
| bash
cat <<EOF | sudo tee /etc/apt/preferences.d/pin-gitlab-runner.pref
Explanation: Prefer GitLab provided packages over the Debian native ones
Package: gitlab-runner
Pin: origin packages.gitlab.com
Pin-Priority: 1001
EOF
apt update
apt install gitlab-runner
```

from <https://docs.gitlab.com/runner/install/linux-repository/>

---

Revision #7

Created 2024-01-26 12:51:56 UTC by magenbrot

Updated 2026-03-03 21:45:38 UTC by magenbrot