

# Spam vorlesen lassen mit espeak

Voraussetzungen:

- Perlmodule: Net::IMAP::Simple, Email::Simple
- espeak-Installation

getestet unter Ubuntu 10.10 Maverick

Dieses Script loggt sich in eine IMAP-Mailbox ein und liest den Betreff aller Mails im SPAM/Junk-Ordner via espeak vor. Die Parameter sollten natürlich entsprechend angepasst werden.

```
#!/usr/bin/perl

use strict;
use warnings;
use Net::IMAP::Simple;
use Email::Simple;

my $server = "mail.domain.de";
my $user = "username";
my $pass = "passwort";
my $folder = "INBOX/Junk";

my $espeak_params = "-s 160";

# open a connection to the IMAP server
my $imap = Net::IMAP::Simple->new($server) || die "Unable to connect to IMAP: $Net::IMAP::Simple::errstr\n";

# login
if(!$imap->login($user, $pass)) {
    print STDERR $imap->errstr . "\n";
    exit(64);
}

# select the SPAM-folder
my $nm = $imap->select($folder);

for(my $i = 1; $i <= $nm; $i++){
    my $es = Email::Simple->new(join "", @{$imap->top($i) } );
    if($imap->seen($i)){
```

```
# already read mail
print "*";
} else {
    # new mail
    print " ";
    # uncomment this to only read new mail
    #my @args = ("espeak", $espeak_param, "\"" . $es->header('Subject') . "\"");
    #system(@args) || die("system @args failed: $?");
}
# print the mailnumber and subject
printf("[%03d] %s\n", $i, $es->header('Subject'));

# comment this out, when you've enabled the read of unread mails only above
my @args = ("espeak", $espeak_params, "\"" . $es->header('Subject') . "\"");
system(@args) || die("system @args failed: $?");
}

$imap->quit;
```

---

Revision #1

Created 27 July 2021 10:00:53 by magenbrot

Updated 27 July 2021 10:01:08 by magenbrot