

# PHP

- HTTP\_POST\_VARS fehlen in PHP5
- "pecl install" endet mit memory size exhausted

# HTTP\_POST\_VARS fehlen in PHP5

Ab PHP5 werden die HTTP\_POST\_VARS nicht mehr zur Verfügung gestellt. Falls man unter keinen Umständen darauf verzichten kann hat man folgende Möglichkeiten:

1. nur noch folgende Variablen als Ersatz verwenden, dies erfordert die Anpassung aller Skripten. Das ist der empfohlene Weg.

```
$_POST als Ersatz für $HTTP_POST_VARS
$_GET als Ersatz für $HTTP_GET_VARS
$_COOKIE als Ersatz für $HTTP_COOKIE_VARS
$_SERVER als Ersatz für $HTTP_SERVER_VARS
```

2. folgenden Code in die Skripte einbinden:

```
$HTTP_POST_VARS = !empty($HTTP_POST_VARS) ? $HTTP_POST_VARS : $_POST;
$HTTP_GET_VARS = !empty($HTTP_GET_VARS) ? $HTTP_GET_VARS : $_GET;
$HTTP_COOKIE_VARS = !empty($HTTP_COOKIE_VARS) ? $HTTP_COOKIE_VARS : $_COOKIE;
$HTTP_SERVER_VARS = !empty($HTTP_SERVER_VARS) ? $HTTP_SERVER_VARS : $_SERVER;
```

3. Aktivieren von register\_long\_arrays in der php.ini. Dies ist nicht empfohlen, die HTTP\_POST\_VARS werden ab PHP6 vollständig entfernt.

# "pecl install" endet mit memory size exhausted

das hat zwar nichts mit der Programmierung zu tun, ist aber eine böse Stolperfalle: Um locking Probleme während eines php-Upgrades zu verhindern ignoriert pecl eine vorhandene php.ini und läuft mit einem default-Wert für memory\_limit von nur 8MB.

Dadurch schlägt z.B. die Installation von dbx fehl:

```
[root@linux pear]# pecl install dbx
pecl/dbx can optionally use PHP extension "mysql"
pecl/dbx can optionally use PHP extension "odbc"
pecl/dbx can optionally use PHP extension "pgsql"
pecl/dbx can optionally use PHP extension "mssql"
pecl/dbx can optionally use PHP extension "fbsql"
pecl/dbx can optionally use PHP extension "oci8"
pecl/dbx can optionally use PHP extension "sybase_ct"
pecl/dbx can optionally use PHP extension "sqlite"
downloading dbx-1.1.0.tgz ...
Starting to download dbx-1.1.0.tgz (30,872 bytes)
.....done: 30,872 bytes

Fatal error: Allowed memory size of 8388608 bytes exhausted (tried to allocate 92160 bytes) in
/usr/share/pear/PEAR/PackageFile/v2/Validator.php on line 171
```

php-devel gcc Achtung: Die Installation von PHP-Extension setzt einen installierten Compiler und das php-devel Paket voraus(wegen dem Kommando phpize):

```
[root@linux pear]# yum -y install php-devel gcc gcc-c++
```

Um diese Einschränkung zu umgehen kann das Paket auch mit pear installiert werden:

```
[root@linux pear]# pear install pecl/dbx
pecl/dbx can optionally use PHP extension "pgsql"
pecl/dbx can optionally use PHP extension "mssql"
pecl/dbx can optionally use PHP extension "fbsql"
pecl/dbx can optionally use PHP extension "oci8"
pecl/dbx can optionally use PHP extension "sybase_ct"
pecl/dbx can optionally use PHP extension "sqlite"
downloading dbx-1.1.0.tgz ...
```

Starting to download dbx-1.1.0.tgz (30,872 bytes)  
.....done: 30,872 bytes  
22 source files, building  
running: phpize  
Configuring for:  
PHP Api Version: 20041225  
Zend Module Api No: 20050922  
Zend Extension Api No: 220051025  
building in /var/tmp/pear-build-root/dbx-1.1.0  
running: /tmp/pear/download/dbx-1.1.0/configure  
checking for egrep... grep -E  
checking for a sed that does not truncate output... /bin/sed  
checking for gcc... gcc  
checking for C compiler default output file name... a.out  
checking whether the C compiler works... yes  
checking whether we are cross compiling... no  
checking for suffix of executables...  
checking for suffix of object files... o  
checking whether we are using the GNU C compiler... yes  
checking whether gcc accepts -g... yes  
checking for gcc option to accept ANSI C... none needed  
checking whether gcc and cc understand -c and -o together... yes  
checking if compiler supports -R... no  
checking if compiler supports -Wl,-rpath,... yes  
checking build system type... x86\_64-redhat-linux-gnu  
checking host system type... x86\_64-redhat-linux-gnu  
checking target system type... x86\_64-redhat-linux-gnu  
checking for PHP prefix... /usr  
checking for PHP includes... -I/usr/include/php -I/usr/include/php/main -I/usr/include/php/TSRM -  
I/usr/include/php/Zend -I/usr/include/php/ext  
checking for PHP extension directory... /usr/lib64/php/modules  
checking for PHP installed headers prefix... /usr/include/php  
checking for re2c... no  
configure: WARNING: You will need re2c 0.9.11 or later if you want to regenerate PHP parsers.  
checking for gawk... gawk  
checking whether to enable dbx support... yes, shared  
checking for ld used by gcc... /usr/bin/ld  
checking if the linker (/usr/bin/ld) is GNU ld... yes  
checking for /usr/bin/ld option to reload object files... -r  
checking for BSD-compatible nm... /usr/bin/nm -B

checking whether In -s works... yes  
checking how to recognise dependent libraries... pass\_all  
checking how to run the C preprocessor... gcc -E  
checking for ANSI C header files... yes  
checking for sys/types.h... yes  
checking for sys/stat.h... yes  
checking for stdlib.h... yes  
checking for string.h... yes  
checking for memory.h... yes  
checking for strings.h... yes  
checking for inttypes.h... yes  
checking for stdint.h... yes  
checking for unistd.h... yes  
checking dlfcn.h usability... yes  
checking dlfcn.h presence... yes  
checking for dlfcn.h... yes  
checking for g++... no  
checking for c++... no  
checking for gpp... no  
checking for aCC... no  
checking for CC... no  
checking for cxx... no  
checking for cc++... no  
checking for cl... no  
checking for FCC... no  
checking for KCC... no  
checking for RCC... no  
checking for xLC\_r... no  
checking for xLC... no  
checking whether we are using the GNU C++ compiler... no  
checking whether g++ accepts -g... no  
checking for g77... no  
checking for f77... no  
checking for xlf... no  
checking for frt... no  
checking for pgf77... no  
checking for fort77... no  
checking for fl32... no  
checking for af77... no  
checking for f90... no

checking for xlf90... no  
checking for pgf90... no  
checking for epcf90... no  
checking for f95... no  
checking for fort... no  
checking for xlf95... no  
checking for ifc... no  
checking for efc... no  
checking for pgf95... no  
checking for lf95... no  
checking for gfortran... no  
checking whether we are using the GNU Fortran 77 compiler... no  
checking whether accepts -g... no  
checking the maximum length of command line arguments... 32768  
checking command to parse /usr/bin/nm -B output from gcc object... ok  
checking for objdir... .libs  
checking for ar... ar  
checking for ranlib... ranlib  
checking for strip... strip  
checking if gcc supports -fno-rtti -fno-exceptions... no  
checking for gcc option to produce PIC... -fPIC  
checking if gcc PIC flag -fPIC works... yes  
checking if gcc static flag -static works... yes  
checking if gcc supports -c -o file.o... yes  
checking whether the gcc linker (/usr/bin/ld -m elf\_x86\_64) supports shared libraries... yes  
checking whether -lc should be explicitly linked in... no  
checking dynamic linker characteristics... GNU/Linux ld.so  
checking how to hardcode library paths into programs... immediate  
checking whether stripping libraries is possible... yes  
checking if libtool supports shared libraries... yes  
checking whether to build shared libraries... yes  
checking whether to build static libraries... no  
configure: creating libtool  
appending configuration tag "CXX" to libtool  
appending configuration tag "F77" to libtool  
configure: creating ./config.status  
config.status: creating config.h  
running: make  
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -I. -I/tmp/pear/download/dbx-1.1.0 -  
DPHP\_ATOM\_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -I/var/tmp/pear-build-root/dbx-1.1.0/main -

```

l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -l/usr/include/php/main -l/usr/include/php/TSRM -
l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx.c
-o dbx.lo
mkdir .libs
gcc -l. -l/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -
l/var/tmp/pear-build-root/dbx-1.1.0/main -l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -
l/usr/include/php/main -l/usr/include/php/TSRM -l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx.c -fPIC -DPIC -o .libs/dbx.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -l. -l/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -l/var/tmp/pear-build-root/dbx-1.1.0/main -
l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -l/usr/include/php/main -l/usr/include/php/TSRM -
l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_mysql.c -o dbx_mysql.lo
gcc -l. -l/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -
l/var/tmp/pear-build-root/dbx-1.1.0/main -l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -
l/usr/include/php/main -l/usr/include/php/TSRM -l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_mysql.c -fPIC -DPIC -o .libs/dbx_mysql.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -l. -l/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -l/var/tmp/pear-build-root/dbx-1.1.0/main -
l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -l/usr/include/php/main -l/usr/include/php/TSRM -
l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_odbc.c -o dbx_odbc.lo
gcc -l. -l/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -
l/var/tmp/pear-build-root/dbx-1.1.0/main -l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -
l/usr/include/php/main -l/usr/include/php/TSRM -l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_odbc.c -fPIC -DPIC -o .libs/dbx_odbc.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -l. -l/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -l/var/tmp/pear-build-root/dbx-1.1.0/main -
l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -l/usr/include/php/main -l/usr/include/php/TSRM -
l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_pgsql.c -o dbx_pgsql.lo
gcc -l. -l/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -
l/var/tmp/pear-build-root/dbx-1.1.0/main -l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -
l/usr/include/php/main -l/usr/include/php/TSRM -l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_pgsql.c -fPIC -DPIC -o .libs/dbx_pgsql.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -l. -l/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -l/var/tmp/pear-build-root/dbx-1.1.0/include -l/var/tmp/pear-build-root/dbx-1.1.0/main -
l/tmp/pear/download/dbx-1.1.0 -l/usr/include/php -l/usr/include/php/main -l/usr/include/php/TSRM -
l/usr/include/php/Zend -l/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_mssql.c -o dbx_mssql.lo

```

```

gcc -I. -I/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -
I/var/tmp/pear-build-root/dbx-1.1.0/main -I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -
I/usr/include/php/main -I/usr/include/php/TSRM -I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_mssql.c -fPIC -DPIC -o .libs/dbx_mssql.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -I. -I/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -I/var/tmp/pear-build-root/dbx-1.1.0/main -
I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -I/usr/include/php/main -I/usr/include/php/TSRM -
I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_fbsql.c -o dbx_fbsql.lo
gcc -I. -I/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -
I/var/tmp/pear-build-root/dbx-1.1.0/main -I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -
I/usr/include/php/main -I/usr/include/php/TSRM -I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_fbsql.c -fPIC -DPIC -o .libs/dbx_fbsql.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -I. -I/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -I/var/tmp/pear-build-root/dbx-1.1.0/main -
I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -I/usr/include/php/main -I/usr/include/php/TSRM -
I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_oci8.c -o dbx_oci8.lo
gcc -I. -I/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -
I/var/tmp/pear-build-root/dbx-1.1.0/main -I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -
I/usr/include/php/main -I/usr/include/php/TSRM -I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_oci8.c -fPIC -DPIC -o .libs/dbx_oci8.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -I. -I/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -I/var/tmp/pear-build-root/dbx-1.1.0/main -
I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -I/usr/include/php/main -I/usr/include/php/TSRM -
I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_sybase.c -o dbx_sybase.lo
gcc -I. -I/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -
I/var/tmp/pear-build-root/dbx-1.1.0/main -I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -
I/usr/include/php/main -I/usr/include/php/TSRM -I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_sybase.c -fPIC -DPIC -o .libs/dbx_sybase.o
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=compile gcc -I. -I/tmp/pear/download/dbx-1.1.0 -
DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -I/var/tmp/pear-build-root/dbx-1.1.0/main -
I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -I/usr/include/php/main -I/usr/include/php/TSRM -
I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H -g -O2 -c /tmp/pear/download/dbx-
1.1.0/dbx_sqlite.c -o dbx_sqlite.lo
gcc -I. -I/tmp/pear/download/dbx-1.1.0 -DPHP_ATOM_INC -I/var/tmp/pear-build-root/dbx-1.1.0/include -
I/var/tmp/pear-build-root/dbx-1.1.0/main -I/tmp/pear/download/dbx-1.1.0 -I/usr/include/php -
I/usr/include/php/main -I/usr/include/php/TSRM -I/usr/include/php/Zend -I/usr/include/php/ext -DHAVE_CONFIG_H
-g -O2 -c /tmp/pear/download/dbx-1.1.0/dbx_sqlite.c -fPIC -DPIC -o .libs/dbx_sqlite.o

```



```

/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=link gcc -DPHP_ATOM_INC -I/var/tmp/pear-build-
root/dbx-1.1.0/include -I/var/tmp/pear-build-root/dbx-1.1.0/main -I/tmp/pear/download/dbx-1.1.0 -
I/usr/include/php -I/usr/include/php/main -I/usr/include/php/TSRM -I/usr/include/php/Zend -I/usr/include/php/ext -
DHAVE_CONFIG_H -g -O2 -o dbx.la -export-dynamic -avoid-version -prefer-pic -module -rpath /var/tmp/pear-
build-root/dbx-1.1.0/modules dbx.lo dbx_mysql.lo dbx_odbc.lo dbx_pgsql.lo dbx_mssql.lo dbx_fbsql.lo
dbx_oci8.lo dbx_sybasect.lo dbx_sqlite.lo
gcc -shared .libs/dbx.o .libs/dbx_mysql.o .libs/dbx_odbc.o .libs/dbx_pgsql.o .libs/dbx_mssql.o .libs/dbx_fbsql.o
.libs/dbx_oci8.o .libs/dbx_sybasect.o .libs/dbx_sqlite.o -Wl,-soname -Wl,dbx.so -o .libs/dbx.so
creating dbx.la
(cd .libs && rm -f dbx.la && ln -s ../dbx.la dbx.la)
/bin/sh /var/tmp/pear-build-root/dbx-1.1.0/libtool --mode=install cp ./dbx.la /var/tmp/pear-build-root/dbx-
1.1.0/modules
cp ./libs/dbx.so /var/tmp/pear-build-root/dbx-1.1.0/modules/dbx.so
cp ./libs/dbx.lai /var/tmp/pear-build-root/dbx-1.1.0/modules/dbx.la
PATH="$PATH:/sbin" ldconfig -n /var/tmp/pear-build-root/dbx-1.1.0/modules

```

-----

Libraries have been installed in:

/var/tmp/pear-build-root/dbx-1.1.0/modules

If you ever happen to want to link against installed libraries  
in a given directory, LIBDIR, you must either use libtool, and  
specify the full pathname of the library, or use the ``-LLIBDIR'`  
flag during linking and do at least one of the following:

- add LIBDIR to the ``LD_LIBRARY_PATH'` environment variable  
during execution
- add LIBDIR to the ``LD_RUN_PATH'` environment variable  
during linking
- use the ``-Wl,-rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to ``/etc/ld.so.conf'`

See any operating system documentation about shared libraries for  
more information, such as the `ld(1)` and `ld.so(8)` manual pages.

-----

Build complete.

(It is safe to ignore warnings about tempnam and tmpnam).

running: make INSTALL\_ROOT="/var/tmp/pear-build-root/install-dbx-1.1.0" install

Installing shared extensions: /var/tmp/pear-build-root/install-dbx-1.1.0/usr/lib64/php/modules/

running: find "/var/tmp/pear-build-root/install-dbx-1.1.0" -ls

```

3735577  4 drwxr-xr-x  3 root  root    4096 Sep 26 15:03 /var/tmp/pear-build-root/install-dbx-1.1.0
3735614  4 drwxr-xr-x  3 root  root    4096 Sep 26 15:03 /var/tmp/pear-build-root/install-dbx-1.1.0/usr
3735615  4 drwxr-xr-x  3 root  root    4096 Sep 26 15:03 /var/tmp/pear-build-root/install-dbx-
1.1.0/usr/lib64
3735616  4 drwxr-xr-x  3 root  root    4096 Sep 26 15:03 /var/tmp/pear-build-root/install-dbx-
1.1.0/usr/lib64/php
3735617  4 drwxr-xr-x  2 root  root    4096 Sep 26 15:03 /var/tmp/pear-build-root/install-dbx-
1.1.0/usr/lib64/php/modules
3735613 296 -rwxr-xr-x  1 root  root   298880 Sep 26 15:03 /var/tmp/pear-build-root/install-dbx-
1.1.0/usr/lib64/php/modules/dbx.so

```

Build process completed successfully

Installing '/usr/lib64/php/modules/dbx.so'

install ok: channel://pecl.php.net/dbx-1.1.0

Extension dbx enabled in php.ini

Die Installation packt das Kommando zum Laden der Extension in die erste Zeile der php.ini. Wer das nicht mag, legt das woanders hin, oder erstellt sich in der php.d eine Datei dbx.ini mit folgendem Inhalt (und entfernt die eingefügte Zeile wieder aus der php.ini):

```
# pear install pecl/dbx
```

```
extension="dbx.so"
```

```
[dbx]
```

```
; returned column names can be converted for compatibility reasons
```

```
; possible values for dbx.colnames_case are
```

```
; "unchanged" (default, if not set)
```

```
; "lowercase"
```

```
; "uppercase"
```

```
; the recommended default is either upper- or lowercase, but
```

```
; unchanged is currently set for backwards compatibility
```

```
dbx.colnames_case = "lowercase"
```